



TeeJet Nozzle Body - 5 Outlet 1/2

RTJQJ365C-500-2-NYB



Details

Available with either 3, 4 or 5 spray positions for easy change of spray tips or quick boom flushing. Positive shutoff between each spray position. Automatic spray alignment using flat fan spray tips. Maximum operating pressure 300 psi (20 bar). Available in 1/2", 3/4", or 1" single or double shanks. Includes ChemSaver diaphragm check valve for drip-free shutoff. Standard diaphragm opens at 10 psi (0.7 bar). Standard EPDM diaphragm with Viton available as an option. Also available with optional 56720 ChemSaver air shutoff valve. Durable design mounts body high on boom structure for maximum protection. 2.25 gpm (8.5 l/min) with 5 psi (0.34 bar) pressure drop. Mounts to a 3/8" (9.5 mm) hole drilled in pipe or tubing. Molded hex socket in upper clamp for attaching to flat surfaces. Hinged upper clamp reduces assembly time and fits inside common boom channels.

Specifications

| | |
|--------------|--------|
| Manufacturer | TeeJet |
|--------------|--------|

Complete Turf Equipment Ltd.

4331 Oil Heritage Road Petrolia, N0N 1R0
519-882-2008

<https://completeturf.rrproducts.com/>